ASSEMBLY AND INSTALLATION INSTRUCTIONS FOR ITEM

#134-3/# 135-3/#191-3/#134-4/# 135-4

#191-4/#134-5/# 135-5/#191-5/#134-8

135-8/#191-8#134-12/# 135-12/#191-12

WARNING

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Should any difficulty be experienced, please consult a qualified electrician before installing.

OUTLET BOX Installation steps: GROUND WIRE WIRE CONNECTOR **BLACK WIRE** WHITE WIRE MOUNTING CROSS BAR **SCREW GREEN SCREW** 1. Turn off the electricity at the Fuse or NIPPLE-1 Circuit Breaker before installation. **CANOPY** 2. Attach the Cross Bar to the Outlet Box by using 2PCS of TOP LOOP Mounting Screws upwards. TOP NUT 3. Attached the Loop to the Nipple-2. ADJUSTABLE LOOP 4. There are one set of extra Metal Ball Nuts inside the package, You can change the Crystal Nuts to be the spare metal pieces **CHAIN** to your options, Please adjust the length of Small Nipple from the Side Channels if the Metal Ball Nuts do not fit well. ADJUSTABLE LOOP **CAUTION: PLEASE DO NOT CHANGE THE BALL NUTS** LOOP WHEN THE FIXTURE HANING TO THE CEILING NIPPLE-2 IN CASE THE GLASS FALLING OFF FROM SMALL SCREW THE FRAME. 5. Choose a certain length of the Chain you need, **CENTRAL CLUSTER** and weave the Fixture Wire and the Ground CRYSTAL NUT─► Wire through the Chain links, then 1SET OF SPARE METAL attached one of the Adjustable Loops to the Top **BALL NUTS** Loop and the other one to the Loop. **BULB** 6. Thread the fixture wire and the Ground Wire CANDLE COVER through the Top Nut, Top Loop, Adjustable Loop, SOCKET

7. Make wire connections with Wire Connectors:.

Canopy, Nipple-1 and the Cross Bar in order.

- ----Connect the Wire (W/ marking) from the light to the Black Wire from the Outlet Box.
- ----Connect the Wire (W/O marking) from the light to the White Wire from the Outlet Box.
- ----Attached the Ground Wire and House Ground Wire to the Cross Bar with a Green Screw. Carefully tuck wires back into the Outlet Box.
- 8. Attached the Canopy to the Cross Bar by inserting the Nipple-1, then secure with the Top Loop and Top Nut.

SIDE CHANNEL

- 9.Put the Glass to the Sockets and secure with the Socket Ring then install Bulbs.
 - (Bulbs are not included, please do not exceed the maximum capacity which is recommended on the Candle Cover.)
- 10. Turn on the power at Fuse or Circuit Box and enjoy your new fixture.